Development of Solar Tracking System Based on Thermal Expansion for Enhanced Energy Efficiency

Atul Kankal[1], Mukund Kumar [2]

[1] Department of Mechanical Engineering, AEC Chikhli, India, atulkankal57@gmail.com,+919322196837

[2] Department of Mechanical Engineering, AEC Chikhli, India, drmukundkumar0@gmail.com,
+918709687739

ABSTRACT

This research presents a novel, fully mechanical solar tracking system utilizing thermal expansion principles to enhance photovoltaic (PV) efficiency. Unlike conventional electronic tracking systems that rely on sensors and actuators, this system leverages passive mechanical components such as bimetallic strips, wax expansion cylinders, and gas expansion chambers to dynamically adjust the orientation of solar panels throughout the day. The elimination of electronic components improves reliability, reduces costs, and makes the system particularly suitable for off-grid applications. A small-scale prototype was developed to validate the system's functionality. Experimental results demonstrate a significant increase in solar energy absorption compared to fixed-panel configurations. This research highlights the potential of passive solar tracking mechanisms as a sustainable, cost-effective alternative for maximizing solar energy capture.

INTRODUCTION

Solar energy has emerged as a critical renewable energy source due to its abundance and sustainability [1]. However, the efficiency of solar panels is highly dependent on their alignment with the sun's trajectory. Stationary solar panels capture less sunlight as the sun moves across the sky, leading to suboptimal energy conversion. Solar tracking systems mitigate this issue by continuously adjusting the panel's orientation to maximize solar exposure.

Traditional solar trackers employ electronic sensors, motors, and microcontrollers to maintain solar alignment. While effective, these systems present challenges such as high-power consumption, mechanical wear, and maintenance costs. In remote or off-grid locations, dependence on electronic components limits their practicality.

This research introduces a fully mechanical solar tracking system that operates without electricity. The system relies on thermally responsive materials that expand or contract in response to temperature changes, causing the solar panel to tilt accordingly. By exploring multiple passive tracking mechanisms—bimetallic strips, wax cylinder expansion, and gas chamber displacement this study aims to develop a cost-effective, maintenance-free alternative to conventional electronic trackers.

Objectives:

- Design a fully mechanical solar tracking system utilizing thermal expansion.
- Develop and test a small-scale prototype.
- Evaluate tracking accuracy and energy efficiency improvement over fixed-panel systems.
- Compare different passive tracking mechanisms.

METHODS AND MATERIAL :

The proposed mechanical solar tracker consists of:

- Frame and Support Structure: Plywood, aluminum, or PVC for stability.
- Solar Panel Mounting System: Hinges and brackets for controlled movement.
- Thermal Expansion Mechanisms:

a. Bimetallic Strips: Bend due to differential heating, adjusting the panel.
b. Wax Cylinder Expansion: Heated wax expands, shifting the panel's tilt.
c. Gas Chamber System: Heated gas expands, exerting pressure on a lever to move the panel.

- Pivoting System: Ball bearings and rotary joints for smooth motion
- Counterweights: Assist in returning the panel to its original position at sunset.
- Reflectors (Optional): Aluminum sheets to enhance sunlight exposure.

Small-Scale Prototype Development :

To validate the concept, a tabletop model was constructed using:

Component	Component
Base Frame	Plywood
Solar Panel	Small-scale PV panel
Expansion Mechanism	Bimetallic strips (Copper-Aluminum), Wax cylinders
Pivoting System	Hinges and ball bearings
Counterweights	Metal washers

- Base and Frame: Cardboard and plywood.
- Mini Solar Panel: Toy-grade solar cell.
- Thermal Expansion Mechanism:

- Wax cylinders (paraffin wax-filled plastic tubes)
- Bimetallic strips (copper-aluminum layers)
- Balloon expansion chamber (air-filled balloon in a sealed jar)

- Pivoting System: Toothpicks and small hinges.
- Counterweights: Coins or washers.

- Step-by-Step Assembly Guide:

- Prepare the Base and Frame: Secure vertical support to the base.

- Mount the Solar Panel: Attach the panel with a hinge mechanism.

- Install the Thermal Expansion System: Position the wax tubes, bimetallic strips, or gas chamber.

- Add Counterweights and Reflectors: Improve stability and light capture.

- Test Movement: Place under sunlight and observe adjustments.

Performance Evaluation :

Key performance indicators include:

1. Tracking Accuracy: Measured deviation from optimal sun alignment.
2. Energy Output: Power generation comparison with fixed panels.
3. Material Durability: Performance consistency over multiple cycles.
4. Cost Analysis: Comparison with electronic tracking system

Literature Review :

Overview of Solar Tracking Systems :

Solar tracking systems are widely studied to enhance the efficiency of photovoltaic (PV) panels. Research indicates that a properly designed tracking system can increase solar energy output by 20–40%

compared to fixed panels. Tracking mechanisms are generally categorized into active and passive tracking systems.

Active Solar Trackers: These systems utilize electronic sensors, motors, and microcontrollers to continuously align the panel with the sun. While they achieve higher accuracy, they require external power sources, which can lead to higher operational costs and increased maintenance.

Passive Solar Trackers: These rely on natural forces, such as thermal expansion, gravity, or material deformation, to adjust solar panel orientation. They are cost-effective, require no electricity, and involve minimal maintenance.

Thermal Expansion-Based Solar Tracking :

Thermal expansion principles have been explored in various engineering applications, but their application in solar tracking remains underdeveloped. Key passive tracking mechanisms include:

Bimetallic Strips: A combination of two metals with different thermal expansion coefficients bends in response to temperature changes. This property allows precise angle adjustments in solar panels without external power.

Wax Expansion Systems: Paraffin wax, enclosed in a sealed chamber, expands when heated. This method is used in solar thermal applications and has been investigated for passive tracking.

Gas Expansion Chambers: Heating trapped air or gas causes volume expansion, which can drive a lever system for solar panel movement.

Comparative Analysis of Tracking Methods :

Tracking Type	Power Requirement	Maintenance	Cost	Efficiency
Fixed Panel	None	Very Low	Low	60–70%
Active Tracker	Requires Sensors & Motors	High	Expensive	85–95%
Passive Tracker (Bimetallic, Wax)	None	Low	Affordable	75–85%



Results and Discussion:

Tracking Efficiency:

Experimental observations indicate that the passive solar tracker maintained an average deviation of ±5 degrees, improving solar exposure time by 30-40% compared to a fixed panel.

Energy Output Comparison:

Energy measurements showed a 25-35% increase in power generation due to better sun alignment.

Material Durability:

Bimetallic strips and wax cylinders performed reliably over multiple cycles. The gas expansion system showed sensitivity to environmental temperature variations.

- Cost Analysis:

Component	Passive Tracker Cost (₹)	Electronic Tracker Cost (₹)
Materials	1,500 - 2,000	5,000 - 10,000
Maintenance	Low	High
Power Consumption	None	Continuous
Total Cost	~₹2,500	~₹10,000
Component	Passive Tracker Cost (₹)	Electronic Tracker Cost (₹)

The passive system provides a cost-effective alternative while maintaining reasonable tracking accuracy.



Conclusion and Future Work:

This study successfully demonstrates a fully mechanical solar tracking system based on thermal expansion. Key benefits include cost-effectiveness, minimal maintenance, and zero electricity consumption. Experimental results validate its practicality for small-scale applications and potential scalability.

Future research directions:

- Dual-axis tracking: Enhancing performance in changing seasonal sun angles.
- Advanced materials: Investigating shape-memory alloys for improved response times.
- Large-scale implementation: Assessing feasibility for industrial solar farms.

This research opens new avenues for passive solar tracking, promoting sustainable energy solutions worldwide.

Reference:

1.Krishna Kumar Jaiswal, ChandramaRoyChowdhury, Deepti Yadav, Ravikant Verma, Swapnamoy Dutta, Km Smriti Jaiswal, SangmeshB, Karthik Selva Kumar Karuppasamy,
Renewable and sustainable clean energy development and impact on social, economic, and environmental health,
Energy Nexus,
Volume 7,
2022,
100118,
ISSN 2772-4271,
https://doi.org/10.1016/j.nexus.2022.100118.